




PROGEF Standard Übergangsverschraubung PP-H/Temperguss galvanisiert metrisch Rp

Ausführung:

- Überwurfmutter: PP-H
- Einschraubteil mit Schweissmuffe PP-H metrisch
- Einlegeteil: Temperguss mit parallelem Rohr-Innengewinde Rp
- Dichtung: O-Ring EPDM Nr. 48 41 00



d [mm]	Rp [inch]	PN [bar]	code	SP	weight [kg]
20	1/2	10	727 530 306	1	0,073
25	3/4	10	727 530 307	1	0,118
32	1	10	727 530 308	5	0,199
40	1 1/4	10	727 530 309	1	0,276
50	1 1/2	10	727 530 310	1	0,317
63	2	10	727 530 311	1	0,579

d [mm]	s [mm]	L2 [mm]	L [mm]	D [mm]	G [inch]	z2 [mm]	z1 [mm]	L1 [mm]
20	25	26	48	43	1	10	9	22
25	31	28	50	51	1 1/4	10	7	22
32	38	30	56	58	1 1/2	10	9	26
40	48	34	65	72	2	12	12	31
50	54	39	72	83	2 1/4	14	14	33
63	67	47	82	100	2 3/4	18	11	35

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.piping.georgfischer.com>